

SAFETY DATA SHEET

DATE ISSUED: 5/22/2023

SDS REF. NO: Isotryme 050 Component A



SDS REV NO: 3.0

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT TRADE NAME:	Isotryme 050 (Component A)
PRODUCT USE:	For industrial use. Component(s) for the manufacture of urethane polymers. We recommend that you use this product in a manner consistent with the listed use. If your intended use is not consistent with the stated use, please contact your sales or technical service representative.
MANUFACTURER	Burtin Polymer Innovations 130 E George St Adairsville, GA 30103 678-800-7003
24 HR EMERGENCY TELEPHONE NUMBER	
CHEMTEC (US Transportation):	800-424-9300
CHEMTEC (International Transportation):	202-483-7616



2. HAZARDS AND IDENTIFICATION

CLASSIFICATION:	GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200) Acute toxicity - Category 4 - Inhalation Skin irritation - Category 2 Eye irritation - Category 2B Respiratory sensitization - Category 1 Skin sensitization - Category 1 Specific target organ toxicity - single exposure - Category 3 Specific target organ toxicity - repeated exposure - Category 2 - Inhalation
PICTOGRAMS:	 
SIGNAL WORD:	Danger
HAZARD STATEMENTS:	Causes skin and eye irritation. May cause an allergic skin reaction. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause damage to organs (Respiratory Tract) through prolonged or repeated exposure if inhaled.
PRECAUTIONARY STATEMENTS:	

PREVENTION	Do not breathe mist or vapors. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves. In case of inadequate ventilation wear respiratory protection.
RESPONSE	IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. If experiencing respiratory symptoms: Call a POISON CENTER/ doctor. Take off contaminated clothing and wash before reuse.
STORAGE	Store in a well-ventilated place. Keep container tightly closed. Store locked up.
DISPOSAL	Dispose of contents and/or container to an approved waste disposal plant.

3. COMPOSITION/INFORMATION ON INGREDIENTS

SYNONYMS	Polymeric diphenylmethane diisocyanate This product is a substance.		
SUBSTANCE NAME	Diphenylmethane Diisocyanate, isomers and homologues		
CASRN			
	Component	CASRN	Concentration
	Diphenylmethane Diisocyanate, isomers and homologues	9016-87-9	100%
	4,4'-Methylenediphenyl diisocyanate	101-68-8	>= 30.0 - <= 50.0 %
	Note: CAS 101-68-8 is an MDI isomer that is part of CAS 9016-87-9.		

4. FIRST AID MEASURES

General advice:	First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.
INHALATION:	Move person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.
SKIN:	Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation or rash occurs. Wash clothing before reuse. An MDI skin decontamination study demonstrated that cleaning very soon after exposure is important, and that a polyglycol-based skin cleanser or corn oil may be more effective than soap and water. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands. Suitable emergency safety shower facility should be available in work area.
EYE:	Immediately flush eyes with water; remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.
INGESTION	If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

Most important symptoms and effects, both acute and delayed:	
Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.	
Indication of any immediate medical attention and special treatment needed	
Notes to physician:	
Maintain adequate ventilation and oxygenation of the patient. May cause respiratory sensitization or asthma-like symptoms. Bronchodilators, expectorants and antitussives may be of help. Treat bronchospasm with inhaled beta2 agonist and oral or parenteral corticosteroids. Respiratory symptoms, including pulmonary edema, may be delayed. Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. If you are sensitized to diisocyanates, consult your physician regarding working with other respiratory irritants or sensitizers. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).	

5. FIRE FIGHTING MEASURES	
EXTINGUISHING MEDIA	
SUITABLE EXTINGUISHING MEDIA:	Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function but will be less effective.
UNSUITABLE EXTINGUISHING MEDIA:	Do not use direct water stream. May spread fire.
SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE	
HAZARDOUS COMBUSTION PRODUCTS	During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Nitrogen oxides. Isocyanates. Hydrogen cyanide. Carbon monoxide. Carbon dioxide.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	Material reacts slowly with water, releasing carbon dioxide which can cause pressure buildup and rupture of closed containers. Elevated temperatures accelerate this reaction. Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. Dense smoke is produced when product burns.
ADVICE FOR FIREFIGHTERS	
FIRE FIGHTING PROCEDURES:	Keep people away. Isolate fire and deny unnecessary entry. Stay upwind. Keep out of low areas where gases (fumes) can accumulate. Water is not recommended but may be applied in large quantities as a fine spray when other extinguishing agents are not available. Do not use direct water stream. May spread fire. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Move container from fire area if this is possible without hazard. Use water spray to cool fire-exposed containers and fire-affected zone until fire is out. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Review the "Accidental Release Measures" and the "Ecological Information" sections of this (M)SDS.
SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:	Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves).. Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective

equipment in post-fire or non-fire clean-up situations, see Section 8 of the safety data sheet.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

Isolate area. Keep unnecessary and unprotected personnel from entering the area. Keep personnel out of low areas. Keep upwind of spill. Spilled material may cause a slipping hazard. Ventilate area of leak or spill. If available, use foam to smother or suppress. Refer to section 7, Handling, for additional precautionary measures. See Section 10 for more specific information. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

ENVIRONMENTAL PRECAUTIONS

Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

Do NOT use absorbent materials such as: Cement powder (Note: may generate heat). Do not place in sealed containers. Contain spilled material if possible. Absorb with materials such as: Dirt. Vermiculite. Sand. Clay. Collect in suitable and properly labeled open containers. Suitable containers include: Metal drums. Plastic drums. Polylined fiber pacs. Wash the spill site with large quantities of water. Attempt to neutralize by adding suitable decontaminant solution: Formulation 1: sodium carbonate 5 - 10%; liquid detergent 0.2 - 2%; water to make up to 100%, OR Formulation 2: concentrated ammonia solution 3 - 8%; liquid detergent 0.2 - 2%; water to make up to 100%. If ammonia is used, use good ventilation to prevent vapor exposure. Contact your supplier for clean-up assistance. See Section 13, Disposal Considerations, for additional information.

7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING:

Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Avoid breathing vapor. Wash thoroughly after handling. Use with adequate ventilation. Keep container closed. This material is hygroscopic in nature. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion.

CONDITIONS FOR SAFE STORAGE, INCLUDING INCOMPATIBILITIES:

Do not store product contaminated with water to prevent potential hazardous reaction. Store in a dry place. Protect from atmospheric moisture. See Section 10 for more specific information. Additional storage and handling information on this product may be obtained by calling your sales or customer service contact.

STORAGE STABILITY

Storage Temperature	Storage Period
15 - 35 °C (59 - 95 °F)	6 Month

8. EXPOSURE CONTROLS\PERSONAL PROTECTION

CONTROL PARAMETERS:		If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.	
Component	Regulation	Type of listing	Value
Diphenylmethane Diisocyanate, isomers and homologues	OSHA Z-1	C	0.2 mg/m ³ 0.02 ppm
4,4'-Methylenediphenyl diisocyanate			
	ACGIH	TWA	0.005 ppm
	OSHA Z-1	C	0.2 mg/m ³ 0.02 ppm
EXPOSURE LIMITS:			
ENGINEERING CONTROLS:		Use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations. Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines. Exhaust systems should be designed to move the air away from the source of vapor/aerosol generation and people working at this point. The odor and irritancy of this material are inadequate to warn of excessive exposure.	
PERSONAL PROTECTIVE EQUIPMENT			
EYES AND FACE:		Use chemical goggles.	
SKIN:			
HARD PROTECTION:		Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Butyl rubber. Avoid gloves made of: Neoprene. Polyvinyl chloride ("PVC" or "vinyl"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.	
OTHER PROTECTION:		Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.	
RESPIRATORY:		Atmospheric levels should be maintained below the exposure guideline. When atmospheric levels may exceed the exposure guideline, use an approved air-purifying respirator equipped with an organic vapor sorbent and a particle filter. For situations where the atmospheric levels may exceed the level for which an air-purifying respirator is effective, use a positive-pressure air-supplying respirator (air line or self-contained breathing apparatus). For emergency response or for situations where the atmospheric level is unknown, use an approved positive-pressure self-contained breathing apparatus or positive-pressure air line with auxiliary self-contained air supply. The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.	

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	
PHYSICAL STATE:	Liquid.
COLOR:	Brown.
ODOR:	Musty.
ODOR THRESHOLD:	0.4 ppm Based on Literature for MDI. Odor is inadequate warning of excessive exposure.
pH:	<i>Not applicable</i> substance/mixture reacts with water

MELTING POINT:	No test data available
FREEZING POINT/RANGE:	Forms crystals below 10°C Literature
BOILING POINT (760 mmHg):	decomposes prior to boiling
FLASH POINT:	closed cup >204 °C (399 °F) Literature
EVAPORATION RATE (Butyl Acetate = 1):	No test data available
FLAMMABILITY (Solid/Gas):	Not Applicable
FLAMMABILITY (liquids):	Not expected to be a static-accumulating flammable liquid.
LOWER EXPLOSION LIMIT:	No test data available
UPPER EXPLOSION LIMIT:	No test data available
VAPOR PRESSURE:	< 0.00001 mmHg at 25 °C (77 °F) Literature
RELATIVE VAPOR DENSITY (air = 1):	8.5 Literature
RELATIVE DENSITY (water = 1):	1.23 at 25 °C (77 °F) / 25 °C Literature
WATER SOLUBILITY:	Not Applicable
PARTITION COEFFICIENT: n-octanol/water	Reacts with water.
AUTO-IGNITION TEMPERATURE:	>600 °C (1,112 °F) Literature
DECOMPOSITION TEMPERATURE:	No test data available
DYNAMIC VISCOSITY:	160 - 240 mPa.s at 25 °C (77 °F) ASTM D4889
KINEMATIC VISCOSITY:	No test data available
EXPLOSIVE PROPERTIES:	Not explosive
OXIDIZING PROPERTIES:	No
MOLECULAR WEIGHT:	No test data available
NOTE: The physical data presented above are typical values and should not be construed as a specification.	

10. STABILITY AND REACTIVITY	
REACTIVITY:	Diisocyanates react with many materials and the rate of reaction increases with temperature as well as increased contact; these reactions can become violent. Contact is increased by stirring or if the other material mixes with the diisocyanate. Diisocyanates are not soluble in water and sink to the bottom, but react slowly at the interface. The reaction forms carbon dioxide gas and a layer of solid polyurea. Reaction with water will generate carbon dioxide and heat.
CHEMICAL STABILITY:	Stable under recommended storage conditions. See Storage, Section 7.
POSSIBILITY OF HAZARDOUS REACTIONS:	Can occur. Exposure to elevated temperatures can cause product to decompose and generate gas. This can cause pressure build-up and/or rupturing of closed containers. Polymerization can be catalyzed by: Strong bases. Water.
CONDITIONS TO AVOID:	Exposure to elevated temperatures can cause product to decompose. Generation of gas during decomposition can cause pressure in closed systems. Pressure build-up can be rapid. Avoid moisture. Material reacts slowly with water, releasing carbon dioxide which can cause pressure buildup and rupture of closed containers. Elevated temperatures accelerate this reaction.
INCOMPATIBLE MATERIALS:	Avoid contact with: Acids. Alcohols. Amines. Water. Ammonia. Bases. Metal compounds. Moist air. Strong oxidizers. Diisocyanates react with many materials and the rate of reaction increases with temperature as well as increased contact; these reactions can become violent. Contact is increased by stirring or if the other material mixes with the diisocyanate. Diisocyanates are not soluble in water and sink to the bottom, but react slowly at the interface. The reaction forms carbon dioxide gas and a layer of solid polyurea. Reaction with water will generate carbon dioxide and heat. Avoid contact with metals such as: Aluminum. Zinc. Brass. Tin. Copper. Galvanized metals. Avoid contact with absorbent materials such as: Moist organic absorbents. Avoid unintended contact with polyols. The reaction of polyols and isocyanates generate heat.
HAZARDOUS DECOMPOSITION PRODUCTS:	Decomposition products depend upon temperature, air supply and the presence of other materials.. Gases are released during decomposition.

11. TOXICOLOGICAL INFORMATION

<i>Toxicological information appears in this section when such data is available.</i>	
Information on likely routes of exposure	
Ingestion, Inhalation, Skin contact, Eye contact.	
Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)	
Acute oral toxicity	Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury.
	Typical for this family of materials. LD50, Rat, > 10,000 mg/kg
Information for components:	Diphenylmethane Diisocyanate, isomers and homologues Typical for this family of materials. LD50, Rat, > 10,000 mg/kg
	4,4'-Methylenediphenyl diisocyanate LD50, Rat, > 2,000 mg/kg No deaths occurred at this concentration.
Acute dermal toxicity	Prolonged skin contact is unlikely to result in absorption of harmful amounts.
	Typical for this family of materials. LD50, Rabbit, > 9,400 mg/kg
Information for components:	Diphenylmethane Diisocyanate, isomers and homologues Typical for this family of materials. LD50, Rabbit, > 9,400 mg/kg
	4,4'-Methylenediphenyl diisocyanate LD50, Rabbit, > 9,400 mg/kg
Acute inhalation toxicity	At room temperature, vapors are minimal due to low volatility. However, certain operations may generate vapor or mist concentrations sufficient to cause respiratory irritation and other adverse effects. Such operations include those in which the material is heated, sprayed or otherwise mechanically dispersed such as drumming, venting or pumping. Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and lungs. May cause pulmonary edema (fluid in the lungs.) Effects may be delayed. Decreased lung function has been associated with overexposure to isocyanates.
Typical for this family of materials.	LC50, Rat, 4 Hour, dust/mist, 0.49 mg/l For similar material(s): 4,4'-Methylenediphenyl diisocyanate (CAS 101-68-8). LC50, Rat, 1 Hour, Aerosol, 2.24 mg/l For similar material(s): 2,4'-Diphenylmethane diisocyanate (CAS 5873-54-1). LC50, Rat, 4 Hour, Aerosol, 0.387 mg/l
Information for components:	Diphenylmethane Diisocyanate, isomers and homologues LC50, Rat, 4 Hour, dust/mist, 0.49 mg/l
	For similar material(s): 4,4'-Methylenediphenyl diisocyanate (CAS 101-68-8). LC50, Rat, 1 Hour, Aerosol, 2.24 mg/l
	For similar material(s): 2,4'-Diphenylmethane diisocyanate (CAS 5873-54-1). LC50, Rat, 4 Hour, Aerosol, 0.387 mg/l
	4,4'-Methylenediphenyl diisocyanate LC50, Rat, 1 Hour, dust/mist, 2.24 mg/l
Skin corrosion/irritation	Based on testing for product(s) in this family of materials: Prolonged contact may cause slight skin irritation with local redness. May stain skin.
Information for components:	Diphenylmethane Diisocyanate, isomers and homologues Prolonged contact may cause slight skin irritation with local redness. May stain skin.

	<p>4,4'-Methylenediphenyl diisocyanate Prolonged contact may cause moderate skin irritation with local redness. Repeated contact may cause moderate skin irritation with local redness. May stain skin.</p>
Serious eye damage/eye irritation	<p>Based on testing for product(s) in this family of materials: May cause moderate eye irritation. May cause slight temporary corneal injury.</p>
Information for components:	<p>Diphenylmethane Diisocyanate, isomers and homologues May cause moderate eye irritation. May cause slight temporary corneal injury.</p>
	<p>4,4'-Methylenediphenyl diisocyanate May cause moderate eye irritation. May cause slight temporary corneal injury.</p>
Sensitization	<p>For this family of materials: For skin sensitization: Skin contact may cause an allergic skin reaction. Animal studies have shown that skin contact with isocyanates may play a role in respiratory sensitization.</p>
	<p>For this family of materials: For respiratory sensitization: May cause allergic respiratory reaction. Reexposure to extremely low isocyanate concentrations may cause allergic respiratory reactions in individuals already sensitized. Asthma-like symptoms may include coughing, difficult breathing and a feeling of tightness in the chest. Occasionally, breathing difficulties may be life threatening. Effects may be delayed.</p>
Information for components:	<p>Diphenylmethane Diisocyanate, isomers and homologues Skin contact may cause an allergic skin reaction. Animal studies have shown that skin contact with isocyanates may play a role in respiratory sensitization. May cause allergic respiratory reaction. MDI concentrations below the exposure guidelines may cause allergic respiratory reactions in individuals already sensitized. Asthma-like symptoms may include coughing, difficult breathing and a feeling of tightness in the chest. Occasionally, breathing difficulties may be life threatening.</p>
	<p>4,4'-Methylenediphenyl diisocyanate For skin sensitization: Skin contact may cause an allergic skin reaction. Animal studies have shown that skin contact with isocyanates may play a role in respiratory sensitization. For respiratory sensitization: May cause allergic respiratory reaction. MDI concentrations below the exposure guidelines may cause allergic respiratory reactions in individuals already sensitized. Asthma-like symptoms may include coughing, difficult breathing and a feeling of tightness in the chest. Occasionally, breathing difficulties may be life threatening.</p>
Specific Target Organ Systemic Toxicity (Single Exposure)	<p>May cause respiratory irritation. Route of Exposure: Inhalation Target Organs: Respiratory Tract</p>
Information for components:	<p>Diphenylmethane Diisocyanate, isomers and homologues May cause respiratory irritation. Route of Exposure: Inhalation Target Organs: Respiratory Tract</p>

	<p>4,4'-Methylenediphenyl diisocyanate May cause respiratory irritation. Route of Exposure: Inhalation Target Organs: Respiratory Tract</p>
Aspiration Hazard	Based on physical properties, not likely to be an aspiration hazard.
Information for components:	<p>Diphenylmethane Diisocyanate, isomers and homologues Based on physical properties, not likely to be an aspiration hazard.</p>
	<p>4,4'-Methylenediphenyl diisocyanate Based on physical properties, not likely to be an aspiration hazard.</p>
Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)	
Specific Target Organ Systemic Toxicity (Repeated Exposure)	For this family of materials: Tissue injury in the upper respiratory tract and lungs has been observed in laboratory animals after repeated excessive exposures to MDI/polymeric MDI aerosols.
Information for components:	<p>Diphenylmethane Diisocyanate, isomers and homologues Tissue injury in the upper respiratory tract and lungs has been observed in laboratory animals after repeated excessive exposures to MDI/polymeric MDI aerosols.</p>
	<p>4,4'-Methylenediphenyl diisocyanate Tissue injury in the upper respiratory tract and lungs has been observed in laboratory animals after repeated excessive exposures to MDI/polymeric MDI aerosols.</p>
Carcinogenicity	For this family of materials: Lung tumors have been observed in laboratory animals exposed to respirable aerosol droplets of MDI/Polymeric MDI (6 mg/m3) for their lifetime. Tumors occurred concurrently with respiratory irritation and lung injury. Current exposure guidelines are expected to protect against these effects reported for MDI.
Information for components:	<p>Diphenylmethane Diisocyanate, isomers and homologues Lung tumors have been observed in laboratory animals exposed to respirable aerosol droplets of MDI/Polymeric MDI (6 mg/m3) for their lifetime. Tumors occurred concurrently with respiratory irritation and lung injury. Current exposure guidelines are expected to protect against these effects reported for MDI.</p>
	<p>4,4'-Methylenediphenyl diisocyanate Lung tumors have been observed in laboratory animals exposed to respirable aerosol droplets of MDI/Polymeric MDI (6 mg/m3) for their lifetime. Tumors occurred concurrently with respiratory irritation and lung injury. Current exposure guidelines are expected to protect against these effects reported for MDI.</p>
Teratogenicity	For this family of materials: In laboratory animals, MDI/polymeric MDI did not cause birth defects; other fetal effects occurred only at high doses which were toxic to the mother.
Information for components:	<p>Diphenylmethane Diisocyanate, isomers and homologues In laboratory animals, MDI/polymeric MDI did not cause birth defects; other fetal effects occurred only at high doses which were toxic to the mother.</p>
	<p>4,4'-Methylenediphenyl diisocyanate Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Did not cause birth defects in laboratory animals.</p>
Reproductive toxicity	No specific, relevant data available for assessment.
Information for components:	<p>Diphenylmethane Diisocyanate, isomers and homologues No relevant data found.</p>
	<p>4,4'-Methylenediphenyl diisocyanate No relevant data found.</p>

Mutagenicity	For this family of materials: Genetic toxicity data on MDI are inconclusive. MDI was weakly positive in some in vitro studies; other in vitro studies were negative. Animal mutagenicity studies were predominantly negative.
Information for components:	Diphenylmethane Diisocyanate, isomers and homologues Genetic toxicity data on MDI are inconclusive. MDI was weakly positive in some in vitro studies; other in vitro studies were negative. Animal mutagenicity studies were predominantly negative.
	4,4'-Methylenediphenyl diisocyanate Genetic toxicity data on MDI are inconclusive. MDI was weakly positive in some in vitro studies; other in vitro studies were negative. Animal mutagenicity studies were predominantly negative.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity	
Acute toxicity to fish	The measured ecotoxicity is that of the hydrolyzed product, generally under conditions maximizing production of soluble species. Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested). LC50, Danio rerio (zebra fish), static test, 96 Hour, > 1,000 mg/l, OECD Test Guideline 203 or Equivalent
Acute toxicity to aquatic invertebrates	EC50, Daphnia magna (Water flea), static test, 24 Hour, > 1,000 mg/l, OECD Test Guideline 202 or Equivalent
Acute toxicity to algae/aquatic plants	NOEC, Desmodesmus subspicatus (green algae), static test, 72 Hour, Growth rate inhibition, 1,640 mg/l, OECD Test Guideline 201 or Equivalent
Toxicity to bacteria	EC50, activated sludge, static test, 3 Hour, Respiration rates., > 100 mg/l
Toxicity to soil-dwelling organisms	EC50, Eisenia fetida (earthworms), 14 d, > 1,000 mg/kg
Toxicity to terrestrial plants	EC50, Avena sativa (oats), Growth inhibition, 1,000 mg/l EC50, Lactuca sativa (lettuce), Growth inhibition, 1,000 mg/l
Persistence and degradability	
Biodegradability:	In the aquatic and terrestrial environment, material reacts with water forming predominantly insoluble polyureas which appear to be stable. In the atmospheric environment, material is expected to have a short tropospheric half-life, based on calculations and by analogy with related diisocyanates. 10-day Window: Not applicable
Biodegradation:	0 %
Exposure time:	28 d
Method:	OECD Test Guideline 302C or Equivalent
Bioaccumulative potential	
Bioconcentration factor (BCF):	92 Cyprinus carpio (Carp) 28 d
Diphenylmethane Diisocyanate, isomers and homologues	
Bioaccumulation:	Bioconcentration potential is low (BCF < 100 or Log Pow < 3). Reacts with water. In the aquatic and terrestrial environment, movement is expected to be limited by its reaction with water forming predominantly insoluble polyureas.
Bioconcentration factor (BCF):	92 Cyprinus carpio (Carp) 28 d
4,4'-Methylenediphenyl diisocyanate	
Bioaccumulation:	Bioconcentration potential is low (BCF < 100 or Log Pow < 3). Reacts with water. In the aquatic and terrestrial environment, movement is expected to be limited by its reaction with water forming predominantly insoluble polyureas.
Bioconcentration factor (BCF):	92 Cyprinus carpio (Carp) 28 d
Mobility in soil	In the aquatic and terrestrial environment, movement is expected to be limited by its reaction with water forming predominantly insoluble polyureas.

13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

DISPOSAL METHOD:

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Recycler. Reclaimer. Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

14. TRANSPORT INFORMATION

DOT

Proper shipping name	Environmentally hazardous substance, liquid, n.o.s.(MDI)
UN number	UN 3082
Class	9
Packing group	III
Reportable Quantity	MDI
Classification for SEA transport (IMO-IMDG):	Not regulated for transport
Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code	Consult IMO regulations before transporting ocean bulk
Classification for AIR transport (IATA/ICAO):	Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Acute toxicity (any route of exposure)
Respiratory or skin sensitisation
Specific target organ toxicity (single or repeated exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This product contains the following substances which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and which are listed in 40 CFR 372.

Components	CASRN
Diphenylmethane Diisocyanate, isomers and homologues	9016-87-9
4,4'-Methylenediphenyl diisocyanate	101-68-8

Pennsylvania Worker and Community Right-To-Know Act:
To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.
California Prop. 65
This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.
United States TSCA Inventory (TSCA)
All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Legend	
ACGIH	USA. ACGIH Threshold Limit Values (TLV)
C	Ceiling
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
STEL	Short term exposure limit
TWA	Time weighted average

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bio accumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bio accumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

Burtin Polymer Innovations urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The

information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.